Field Report for 2016 SPME Porewater Sampling and Surface Sediment Sampling River Mile 10.9 Removal Action Lower Passaic River Study Area

December 8, 2016

This field report describes the solid-phase microextraction (SPME) porewater sampling and surface sediment sampling performed of the cap at the River Mile 10.9 (RM 10.9) Removal Area. The SPME samplers were deployed over three days in June 2016 and were recovered over three days in August 2016. During SPME sampler recovery, samples of surface sediments that had accumulated since cap construction were also collected. A representative of Region 2 (from CDM Smith) was present during all field activities. This field report also describes the visual cap inspection performed over two days in July 2016. This work was performed as described in the Lower Passaic River Study Area River Mile 10.9 Post-Construction Monitoring Quality Assurance Project Plan, Revision 2 (QAPP) submitted to US EPA Region 2 (Region 2) on April 12, 2016 and the draft River Mile 10.9 Removal Action Long-Term Monitoring and Maintenance Plan, Revision 2, submitted to Region 2 on April 12, 2016 (LTMMP). A subsequent revision to the QAPP (Revision 3) was submitted to Region 2 on August 18, 2016 and a subsequent revision to the LTMMP (Revision 3) was submitted to Region 2 on September 2, 2016. These documents are under Region 2 review.

SPME Porewater Sampling and Surface Sediment Sampling

SPME Sampler Deployment

SPME samplers were installed at ten sampling stations over three days from June 3 to 5, 2016. The sampler locations are shown on Figure 1. The samplers were installed at all locations by walking on the cap. The dates for sampler installation were selected at a monthly (lunar) low tide to maximize the area of the cap that could be accessed by foot. For the same reason, the times for sampler installation were selected at daytime low tides. Two sampler locations (609 and 610) could not be accessed by foot because the cap is narrow in this area and there is a fence near the shore. These two sampler locations, therefore, were accessed from a boat. Once at these locations, both were accessible for sampler installation by walking on the cap. Location 609 was underwater during the installation and because the water level rose rapidly, it was difficult to determine the thicknesses of all the cap layers at that location.

The SPME samplers were installed to monitor three units. These units and the associated proposed depth intervals from deep to shallow, as noted in the QAPP, are as follows:

- underlying sediments (approximately 31 to 36 inches below the top of the cap),
- cap active layer (approximately 15 to 20 inches below the top of the cap), and
- armor layer (approximately 2 to 7 inches below the top of the cap).

These proposed depths are approximate and are based on the specifications of the constructed cap. Probing and resistance to driving the samplers were used to approximate the depths and thicknesses of these units. Typically the top of the armor layer and the presence of the geotextile liner (bottom of armor layer and top of the cap active layer) could be distinguished. However, the contact between the cap active layer and underlying sediments could not be distinguished. Therefore, the target depth for the top of the screened interval of the active layer samplers was immediately below the geotextile and the top of the screened interval of the underlying sediment samplers was 16 inches below the geotextile based on the as-constructed thickness of the active layer (approximately 10 inches) plus 6 inches. Table 1 presents the porewater sampler installed depths. It also presents the estimated thicknesses of the surface sediment, habitat layer (if distinguishable from sediment), and armor layer, and the depth to the geotextile.

AECOM 1 December 2016

To avoid cross-contamination between depth intervals, each SPME sampler was deployed in a separate sampler and samplers were not stacked in one borehole. To the extent possible the samplers were inserted into the cap in a triangular pattern (one for each of the three depths). They were installed as close as possible and within approximately 2 feet of each other. The actual locations of the samplers depended on the results of probing conducted at the time of deployment and ability to penetrate to the desired depth.

Each SPME sampler consisted of nine SPME fibers of 15 centimeter length attached with polytetrafluoroethylene (PTFE) tape to a 1/8 inch diameter stainless steel rod. The fibers and rods were inserted into a Henry Sampler that was modified by the manufacturer by cutting additional slots into the sampler so that there was a 6-inch slotted interval. This 6-inch slotted interval matches the six inch screened interval of the AMS Soil Vapor Probes drive point tips used to install the samplers. The Henry Samplers were also manufactured without the cross T handles so that they could be sealed from surface water. The AMS Soil Vapor Probes with disposable drive point tips were advanced by driving with a slide hammer through the sediment to the desired sample depth. Following installation, the Henry Samplers were placed in the AMS Soil Vapor Probe casing which was then removed leaving the screened disposable tip and the Henry Sampler. The soft sediments at the surface collapsed around the Henry Samplers. A 4-inch diameter steel plate with set screw was then installed on the Henry Sampler with the steel plate resting on the sediment. The Henry sampler was then cut down to as close as possible to the sediment surface (generally less than six inches above the sediment surface), filled with deionized (DI) water, and then capped to prevent surface water from entering the sampler. Samplers were flagged with colored tape to indicate sampler depth.

Quality control samples included duplicate samples at each sample interval at location 603. The duplicate samples were installed in separate boreholes approximately 18 inches from the primary set of samplers. Additionally, one field blank was prepared and stored for the duration of the deployment. The photographic log from the sampler installation is included in Attachment A.

Midpoint Check

Midpoint checks of the samplers were performed at low tide over two days on July 6 to 7, 2016. All samplers were present and in good shape. Only small trash, such as plastic bags were snagged on some samplers. A few samplers were missing the sampler depth color tape and the tape was replaced as needed. For the most part, the metal disks placed around each sampler were covered with sediment but no significant accumulation was observed. All samplers were photographed and the photograph log is included in Attachment B.

Check after a Large Rain Event

On August 3, 2016, the samplers were checked from shore at low tide after a large rain event. All locations that were visible from shore appeared to be undamaged although some had acquired some small debris. The photograph log from this check is included in Attachment C.

Sampler Recovery

The SPME samplers were recovered over three days between August 19 and 22, 2016, approximately 75 to 79 days after deployment which conservatively exceeded the planned deployment duration of 60 days. Similar to sampler deployment, the samplers were recovered at a monthly low tide and at daily low tides. Additionally, all samplers were recovered by walking on the cap. Locations 609 and 610 were accessed by boat but the samplers were retrieved by walking on the cap. The photographic log from the sampler recovery is included in Attachment D.

Prior to sampler removal at each location, a surface sediment sample was collected. The surface sediment samples were located within 8 inches horizontally of the armor layer sampler at each location.

These samples were collected with clean stainless steel spoons into sample jars and homogenized within the sample jar. A composite of soft sediment from the surface to the top of the habitat layer of the cap was collected for analysis at locations where newly deposited soft sediment was present. There was no soft sediment at station 0608, so a sample of the top three inches of material was collected.

Prior to removal of each sampler, the height of the sampler above the sediment surface was measured. Soft sediment accumulated in small amounts (generally less than one inch) around several of the Henry Samplers during the course of the deployment. Upon removal, the Henry Sampler was rinsed with DI water to remove any sediment adhering to the outside of the sampler. The length of the sampler was then measured and the depth of the sample interval was determined by subtracting the height of the sampler above the sediment surface from the length of the sampler. The samplers were then wrapped in aluminum foil and transported to a processing area established on shore. The depths of the samplers at recovery are presented in Table 1.

At the processing area, the SPME fibers were removed from each sampler. The fibers were then rinsed with DI water. Where possible, the portions of fibers in contact with the PTFE tape were cut and removed and the total length of recovered fibers from each sampler was measured. These fiber lengths are included in Table 2.

Analytical Results

The SPME fibers and the surface sediment were analyzed for the following three constituents using the following analytical methods:

- 2,3,7,8-Tetrachlorodibenzo-p-dioxin (2,3,7,8-TCDD) using USEPA Method 1613B
- 2,2',5,5'-Tetrachlorobiphenyl (PCB 52) using USEPA Method 1668C
- Phenanthrene using modified California USEPA Air Resources Board Method 429

The SPME samples were analyzed by SGS-North America in Wilmington, NC. High Resolution Gas Chromatography and High Resolution Mass Spectrometry (HRMS/HRGC) and isotope dilution were used to maximize the analytical sensitivity and accuracy. Analyte mass in the SPME fibers was reported by the laboratory on a picogram (pg)/sample basis. The results for analyte mass were converted to porewater concentrations using values for partition coefficients for the polydimethylsiloxane (PDMS) sorbent presented in the QAPP. The SPME analytical results and calculated porewater concentrations are presented in Table 2. An example calculation is presented in Attachment E.

Visual Cap Inspection

A visual inspection of the cap was performed over two days on July 6 to 7, 2016 and concurrent with the SPME sampler mid-point check. This visual inspection included the following activities:

- Poling to confirm the presence of the armor layer along a series of transects oriented perpendicular to the shore; and
- Photographing the cap at low tide from the boat and from the shore.

Poling was performed during higher tides from a boat and at lower tides on foot.

Poling from the Boat

Poling from the boat was conducted over the course of two days on July 6 to 7, 2016. Poling was performed from the approximate locations of the SPME samplers to edge of the cap at the river channel. A long metal rod marked with tape every six inches was lowered into the water at locations along each transect. The coordinates of each poling location were measured with a GPS. Observations were recorded at each poled location of the depth of surface water over the sediment surface and the presence/absence of armor stone. Where possible, the depth to soft sediment and/or the habitat layer

above the armor stone were also recorded. Attempts were made to collect all three measurements (water depth, soft sediment thickness, habitat layer thickness) at coincident locations, however because the boat could only be maintained on location by adjusting the motor speed and direction, there is some spread in the measurement locations. The results of the poling are presented in Table 3.

Poling on Foot

Poling on foot was conducted during low tide on July 7, 2016. Poling was performed from the shore to each SPME location. Similar to the boat-based poling, GPS coordinates were collected at each of the onfoot poling locations and observations were made of the soft sediment thickness, habitat layer thickness and presence/absence of the armor layer (Table 3).

Photographic Documentation

The cap was photographed during the visual inspection. Photographs were taken during the morning low tide event on July 7, 2016 concurrent with the on-foot poling and mid-program inspection. The photograph log is included in Attachment F.

Results

Poling was conducted along 12 transects located perpendicular to shore. Ten transects passed through the SPME sampler stations and two transects were located at the approximate upstream and downstream cap boundaries. Figure 2 shows the transect locations and the poling locations.

The number of poling locations at each transect varied based on the transect length and ranged from 4 to 12. A total of 96 locations were poled for the presence of the armor layer. The armor layer was found at all but two locations (adjacent locations on Transect B) near the navigation channel. At these two locations, it is believed that the pole was pushed through the sand layer and encountered the geotextile. The armor layer appeared less dense at one additional location (end of Transect E) also near the navigation channel and possibly at the edge of or off the cap. At this location the armor layer was encountered by moving the poling rod a short distance (approximately one foot or less). These locations are shown on Figure 2.

Tables

AECOM December 2016

Table 1
Porewater Sampler Depths and Probing Results

Location	Sampler	Sampler ID	Soft Sediment Thickness (in)	Habitat Layer Thickness (in)	Armor Layer Thickness (in)	Geotextile Depth (in)	Depth to Bottom of Sampler, Deployment (in)	Depth to Bottom of Sampler, Retrieval (in)
	Armor	16A-0601-E1-AS	5	1	5.5	11.5	11.5	11.5
601	Active	16A-0601-E2-BS	5	1	5.5	11.5	18.5	15.75
	Sediment	16A-0601-E3-CS	5	1	5.5	11.5	27.5	28.75
	Armor	16A-0602-E1-AS	9.5	0.75	14.75	25	25	24.5
602	Active	16A-0602-E2-BS	9.5	0.75	14.75	25	32	31.5
	Sediment	16A-0602-E3-CS	9.5	0.75	14.75	25	43	42.5
	Armor	16A-0603-E1-AS	11.5	4	5	20.5	20.5	20
603	Active	16A-0603-E2-BS	15	1	5	21	27.5	26.75
	Sediment	16A-0603-E3-CS	12.5	0	10.5	23	40	39.75
	Armor	16A-0603-E1-AT	12	5	3.5	20.5	19.5	19.25
603 dup	Active	16A-0603-E2-BT	11	3.5	6	20.5	27	26
	Sediment	16A-0603-E3-CT	14	2.5	5	21.5	38	38.25
	Armor	16A-0604-E1-AS	18.5	3.5	3	25	23	21.5
604	Active	16A-0604-E2-BS	18.5	3.5	3	25	30.25	29.75
	Sediment	16A-0604-E3-CS	18.5	3.5	3	25	43	42.75
	Armor	16A-0605-E1-AS	10	6	10.5	26.5	25	23.75
605	Active	16A-0605-E2-BS	10.5	0	16	26.5	32.5	31.5
	Sediment	16A-0605-E3-CS	10	4.5	12	26.5	45	41
	Armor	16A-0606-E1-AS	13.5	4	0*	17.5	17.5	19.5
606	Active	16A-0606-E2-BS	13.5	4	0*	17.5	24.5	23.25
	Sediment	16A-0606-E3-CS	NM	NM	4	22	38.5	41
	Armor	16A-0607-E1-AS	7	3.5	0**	10.5	10.5	9.75
607	Active	16A-0607-E2-BS	7	3.5	0**	10.5	17.5	16.75
	Sediment	16A-0607-E3-CS	7	3.5	0**	10.5	32.5	34.75
	Armor	16A-0608-E1-AS	0	4.5	11	15.5	12	12
608	Active	16A-0608-E3-BS	2	3.5	9	14.5	21.5	23.5
	Sediment	16A-0608-E2-CS	1.5	4.5	8	14	32	32
	Armor	16A-0609-E1-AS	17.5	not distinguishable	5.5	23	21.5	20.75
609	Active	16A-0609-E2-BS	NM	NM	NM	27.5	34.5	32
	Sediment	16A-0609-E3-CS	NM	NM	NM	20	38	40.25
	Armor	16A-0610-E1-AS	5	1	4	10	9.5	8.75
610	Active	16A-0610-E2-BS	5	1	4	10	16.5	16.75
	Sediment	16A-0610-E3-CS	5	1	4	10	26.5	26

NM - Not Measured

Screened interval of porewater samplers is 6 inches.

Location 609 was underwater during the installation and because the water level rose rapidly, it was difficult to determine the thicknesses of all the cap layers at that location.

^{*} Armor layer encountered within 6 inches of location.

 $^{**} Additional probing on 6/5/16 \ revealed \ armor \ within 5 \ foot \ radius \ of \ station \ 607 \ installed \ samplers.$

Table 2 **SPME PDMS Sorbent and Surface Sediment Analytical Results**

	16A-0601				16A-0602					
	layer_sampled		Armor Layer	Cap Active Layer	Underlying Sediment	Surface Sediment	Armor Layer	Cap Active Layer	Underlying Sediment	Surface Sediment
	sys_loc_code		16A-0601-E1	16A-0601-E2	16A-0601-E3	16A-0601-S1	16A-0602-E1	16A-0602-E2	16A-0602-E3	16A-0602-S1
	sys_sample_code		16A-0601-E1-AS	16A-0601-E2-BS	16A-0601-E3-CS	16A-0601-S1-AS	16A-0602-E1-AS	16A-0602-E2-BS	16A-0602-E3-CS	16A-0602-S1-AS
S	ample deployment_date		6/4/2016	6/4/2016	6/4/2016	NA	6/5/2016	6/5/2016	6/5/2016	NA
	sample retrival_date	QAPP EDL Estimate	8/20/2016	8/20/2016	8/20/2016	8/20/2016	8/20/2016	8/20/2016	8/20/2016	8/20/2016
	matrix_code		SPME	SPME	SPME	SE	SPME	SPME	SPME	SE
	sample_type_code		N	N	N	N	N	N	N	N
	fiber_length (mm)		1514.9	1594.4	1599.7	-	1598.4	1609.3	1707.5	-
	report_result_unit									
Phenanthrene	1			T		ı		ı	ı	ı
Mass in SPME PDMS Sorbent	ng	9.9	18.3 J+	9.63 J+	5.41 J+	-	6.98 J+	4.86 J+	59.9	=
Concentration in Sediment	ng/g	-	-	-	-	2270 J	-	-	-	2010 J
Calculated Concentration in Porewater	ng/L	-	45 J+	23 J+	13 J+	-	16 J+	11 J+	130	-
PCB-52										
Mass in SPME PDMS Sorbent	pg	45	1740	294	2550	-	388	245	29900	-
Concentration in Sediment	pg/g	-	-	-	-	27100 J	-	-	-	25400 J
Calculated Concentration in Porewater	pg/L	-	84	14	120	-	18	11	1300	-
2,3,7,8-TCDD										
Mass in SPME PDMS Sorbent	pg	17	< 1.84 U	< 2.46 U	< 2.09 U	-	< 3.58 U	< 2.3 U	12.5	=
Concentration in Sediment	pg/g	-	-	-	-	196 J	-	-	-	218 J
Calculated Concentration in Porewater	pg/L	-	< 0.036 U	< 0.045 U	< 0.038 U	-	< 0.065 U	< 0.042 U	0.21	-
Total Organic Carbon										
Total Organic Carbon ²	%					7.00				7.33

Notes:

Sample type: N - sample, FD - field duplicate, FB - field blank Matrix code: SPME - Solid Phase Micro Extraction , SE - sediment

PDMS - polydimethylsiloxane EDL - Estimated Detection Limit

mm - millimeter ng - nanogram

ng/g - nanogram per gram

ng/L - nanogram per liter

pg - picogram

pg/g - picogram per gram

pg/L - picogram per liter

L/kg - liter per kilogram

- U = The analyte was analyzed for, but was not detected above the reported sample detection limit.
- J = The analyte was positively identified; the associated numerical value is the approximate concentration of the analyte in the sample.
- J+ = The analyte was positively identified; the associated numerical value is the approximate concentration of the analyte in the sample and is potentially biased high.
- Z = EMPC-J = The analyte is identified as an estimated maximum possibleconcentration; the associated numerical value is the approximate concentration of the analyte in the sample.
- Samplers installed through overlying water; control of sampler depths and thickness of layers is less certain than at other locations where the samplers were installed without significant overlying water.
- ² Average of duplicate samples

Porewater concentration calculated using equation:

(Mass in SPME PDMS Sorbent/((PI() $^{\circ}$ 0.15 $^{\circ}$ 2)-(PI() $^{\circ}$ 0.10 $^{\circ}$ 2)) *fiber length))/ KPDMS where K_{PDMS} is 6,761 L/kg for phenanthrene, 346,737 L/kg for PCB-52, and 870,964 L/kg for 2,3,7,8-TCDD.

Table 2
SPME PDMS Sorbent and Surface Sediment Analytical Results

	Location		16A-0603 a							
layer_sampled			Armor	Layer	Cap Acti	ve Layer	Underlying	g Sediment	Surface :	Sediment
	sys_loc_code		16A-0603-E1	16A-0603-E1	16A-0603-E2	16A-0603-E2	16A-0603-E3	16A-0603-E3	16A-0603-S1	16A-0603-S1
	sys_sample_code		16A-0603-E1-AS	16A-0603-E1-AT	16A-0603-E2-BS	16A-0603-E2-BT	16A-0603-E3-CS	16A-0603-E3-CT	16A-0603-S1-AS	16A-0603-S1-AT
Sa	ample deployment_date		6/5/2016	6/5/2016	6/5/2016	6/5/2016	6/5/2016	6/5/2016	NA	NA
	sample retrival_date	QAPP EDL Estimate	8/20/2016	8/20/2016	8/20/2016	8/20/2016	8/20/2016	8/20/2016	8/20/2016	8/20/2016
	matrix_code		SPME	SPME	SPME	SPME	SPME	SPME	SE	SE
	sample_type_code		N	FD	N	FD	N	FD	N	FD
	fiber_length (mm)		1549	1623.8	1435.3	1599.8	1593.4	1418.5	-	-
	report_result_unit									
Phenanthrene				1	1	1		T	1	
Mass in SPME PDMS Sorbent	ng	9.9	13.1 J+	11.7 J+	5.15 J+	< 4 U	84.5 J	26.8 J	-	-
Concentration in Sediment	ng/g	-	-	-	-	-	-	-	2180 J	2270 J
Calculated Concentration in Porewater	ng/L	=	32 J+	27 J+	14 J+	< 9.4 U	200 J	71 J	-	-
PCB-52									1	
Mass in SPME PDMS Sorbent	pg	45	691	872	130 J	77.4 J	14900	14900	-	-
Concentration in Sediment	pg/g	-	-	-	-	-	-	-	26300 J	28400 J
Calculated Concentration in Porewater	pg/L	-	33	39	6.7 J	3.6 J	690	770	-	-
2,3,7,8-TCDD	-									
Mass in SPME PDMS Sorbent	pg	17	< 2.23 U	< 4.03 U	< 2.23 U	< 4.58 U	< 2.37 U	10 J	-	-
Concentration in Sediment	pg/g	-	-	-	-	-	-	-	232 J	209 J
Calculated Concentration in Porewater	pg/L	-	< 0.042 U	< 0.073 U	< 0.045 U	< 0.084 U	< 0.043 U	0.21 J	-	-
Total Organic Carbon										
Total Organic Carbon ²	%								7.60	7.33

Notes:

Sample type: N - sample, FD - field duplicate, FB - field blank Matrix code: SPME - Solid Phase Micro Extraction , SE - sediment

PDMS - polydimethylsiloxane EDL - Estimated Detection Limit

mm - millimeter

ng - nanogram

ng/g - nanogram per gram

ng/L - nanogram per liter

pg - picogram

pg/g - picogram per gram

pg/L - picogram per liter

L/kg - liter per kilogram

U = The analyte was analyzed for, but was not detected above the reported sample detection limit.

- J = The analyte was positively identified; the associated numerical value is the approximate concentration of the analyte in the sample.
- J+ = The analyte was positively identified; the associated numerical value is the approximate concentration of the analyte in the sample and is potentially biased high.
- Z = EMPC-J = The analyte is identified as an estimated maximum possible concentration; the associated numerical value is the approximate concentration of the analyte in the sample.
- Samplers installed through overlying water; control of sampler depths and thickness of layers is less certain than at other locations where the samplers were installed without significant overlying water.
- ² Average of duplicate samples

Porewater concentration calculated using equation:

(Mass in SPME PDMS Sorbent/((PI() * 0.15 $^{\circ}$ 2)-(PI() * 0.10 $^{\circ}$ 2)) *fiber length))/ KPDMS where K_{PDMS} is 6,761 L/kg for phenanthrene, 346,737 L/kg for PCB-52, and 870,964 L/kg for 2,3,7,8-TCDD.

Table 2 **SPME PDMS Sorbent and Surface Sediment Analytical Results**

	Location		16A-0604				16A	ı-0605		
	layer_sampled		Armor Layer	Cap Active Layer	Underlying Sediment	Surface Sediment	Armor Layer	Cap Active Layer	Underlying Sediment	Surface Sediment
	sys_loc_code		16A-0604-E1	16A-0604-E2	16A-0604-E3	16A-0604-S1	16A-0605-E1	16A-0605-E2	16A-0605-E3	16A-0605-S1
	sys_sample_code		16A-0604-E1-AS	16A-0604-E2-BS	16A-0604-E3-CS	16A-0604-S1-AS	16A-0605-E1-AS	16A-0605-E2-BS	16A-0605-E3-CS	16A-0605-S1-AS
	sample deployment_date		6/4/2016	6/4/2016	6/4/2016	NA	6/4/2016	6/4/2016	6/4/2016	NA
	sample retrival_date	QAPP EDL Estimate	8/20/2016	8/20/2016	8/20/2016	8/20/2016	8/20/2016	8/20/2016	8/20/2016	8/20/2016
	matrix_code		SPME	SPME	SPME	SE	SPME	SPME	SPME	SE
	sample_type_code		N	N	N	N	N	N	N	N
	fiber_length (mm)		1548.3	1558	1630.4	-	1456.2	1564.3	1458	-
Diversity	report_result_unit									
Phenanthrene		0.0	47.0.1	F 10 I	1 411		04.1	F 70 I	1 411	
Mass in SPME PDMS Sorbent	ng	9.9	17.2 J+	5.18 J+	< 4 U	-	24 J+	5.79 J+	< 4 U	-
Concentration in Sediment	ng/g	-	-	-	-	2230 J	-	-	-	2170 J
Calculated Concentration in Porewater	ng/L	-	42 J+	13 J+	< 9.2 U	-	62 J+	14 J+	< 10 U	-
PCB-52										
Mass in SPME PDMS Sorbent	pg	45	1670	816	1120	-	1100	289	93.1 J+	-
Concentration in Sediment	pg/g	-	-	-	-	24100 J	-	-	-	26100 J
Calculated Concentration in Porewater	pg/L	-	79	38	50	-	55	14	4.7 J+	-
2,3,7,8-TCDD										
Mass in SPME PDMS Sorbent	pg	17	< 6.07 U	< 4.29 U	< 2.28 U	-	< 2.2 U	< 2.36 U	< 2.47 U	-
Concentration in Sediment	pg/g	=	-	-	-	199 J	-	-	-	215 J
Calculated Concentration in Porewater	pg/L	-	< 0.11 U	< 0.081 U	< 0.041 U	·	< 0.044 U	< 0.044 U	< 0.050 U	-
Total Organic Carbon										
Total Organic Carbon ²	%					7.53				7.77

Notes:

Sample type: N - sample, FD - field duplicate, FB - field blank Matrix code: SPME - Solid Phase Micro Extraction , SE - sediment

PDMS - polydimethylsiloxane EDL - Estimated Detection Limit

mm - millimeter ng - nanogram

ng/g - nanogram per gram

ng/L - nanogram per liter

pg - picogram

pg/g - picogram per gram

pg/L - picogram per liter

L/kg - liter per kilogram

- U = The analyte was analyzed for, but was not detected above the reported sample detection limit.
- J = The analyte was positively identified; the associated numerical value is the approximate concentration of the analyte in the sample.
- J+ = The analyte was positively identified; the associated numerical value is the approximate concentration of the analyte in the sample and is potentially biased high.
- Z = EMPC-J = The analyte is identified as an estimated maximum possibleconcentration; the associated numerical value is the approximate concentration of the analyte in the sample.
- Samplers installed through overlying water; control of sampler depths and thickness of layers is less certain than at other locations where the samplers were installed without significant overlying water.
- ² Average of duplicate samples

Porewater concentration calculated using equation:

(Mass in SPME PDMS Sorbent/((PI() $^{\circ}$ 0.15 $^{\circ}$ 2)-(PI() $^{\circ}$ 0.10 $^{\circ}$ 2)) *fiber length))/ KPDMS where K_{PDMS} is 6,761 L/kg for phenanthrene, 346,737 L/kg for PCB-52, and 870,964 L/kg for 2,3,7,8-TCDD.

Table 2 SPME PDMS Sorbent and Surface Sediment Analytical Results

Location				16 <i>A</i>	ı-0606			16 <i>P</i>	16A-0607			
	layer_sampled		Armor Layer	Cap Active Layer	Underlying Sediment	Surface Sediment	Armor Layer	Cap Active Layer	Underlying Sediment	Surface Sediment		
	sys_loc_code		16A-0606-E1	16A-0606-E2	16A-0606-E3	16A-0606-S1	16A-0607-E1	16A-0607-E2	16A-0607-E3	16A-0607-S1		
	sys_sample_code		16A-0606-E1-AS	16A-0606-E2-BS	16A-0606-E3-CS	16A-0606-S1-AS	16A-0607-E1-AS	16A-0607-E2-BS	16A-0607-E3-CS	16A-0607-S1-AS		
Sa	ample deployment_date		6/3/2016	6/3/2016	6/3/2016	NA	6/3/2016	6/3/2016	6/3/2016	NA		
	sample retrival_date	QAPP EDL Estimate	8/19/2016	8/19/2016	8/19/2016	8/19/2016	8/19/2016	8/19/2016	8/19/2016	8/19/2016		
	matrix_code		SPME	SPME	SPME	SE	SPME	SPME	SPME	SE		
	sample_type_code		N	N	N	N	N	N	N	N		
	fiber_length (mm)		1604.3	1560.5	1569.9	-	1635.3	1569.9	1571.6	-		
	report_result_unit											
Phenanthrene	T			1								
Mass in SPME PDMS Sorbent	ng	9.9	22.3 J+	8.74 J+	7.81 J+	-	30.9	4.4 J+	5.34 J+	-		
Concentration in Sediment	ng/g	-	-	-	-	2100 J	-	-	-	1190 J		
Calculated Concentration in Porewater	ng/L	-	52 J+	21 J+	19 J+	-	71	11 J+	13 J+	-		
PCB-52												
Mass in SPME PDMS Sorbent	pg	45	1290	475	2440	-	2790	192	2030	-		
Concentration in Sediment	pg/g	-	-	-	-	22700 J	-	-	-	10100		
Calculated Concentration in Porewater	pg/L	-	59	22	110	-	130	9	95	-		
2,3,7,8-TCDD												
Mass in SPME PDMS Sorbent	pg	17	< 5.19 U	< 9.17 U	< 5.91 U	=	< 5.14 U	< 10.7 U	< 4.48 U	=		
Concentration in Sediment	pg/g	=	-	-	=	225 J	-	-	-	195		
Calculated Concentration in Porewater	pg/L	-	< 0.095 U	< 0.17 U	< 0.11 U	-	< 0.092 U	< 0.20 U	< 0.083 U	-		
Total Organic Carbon												
Total Organic Carbon ²	%					7.20				4.47		

Notes:

Sample type: N - sample, FD - field duplicate, FB - field blank Matrix code: SPME - Solid Phase Micro Extraction , SE - sediment

PDMS - polydimethylsiloxane EDL - Estimated Detection Limit

mm - millimeter ng - nanogram

ng/g - nanogram per gram

ng/L - nanogram per liter

pg - picogram

pg/g - picogram per gram

pg/L - picogram per liter

L/kg - liter per kilogram

- U = The analyte was analyzed for, but was not detected above the reported sample detection limit.
- J = The analyte was positively identified; the associated numerical value is the approximate concentration of the analyte in the sample.
- J+ = The analyte was positively identified; the associated numerical value is the approximate concentration of the analyte in the sample and is potentially biased high.
- Z = EMPC-J = The analyte is identified as an estimated maximum possible concentration; the associated numerical value is the approximate concentration of the analyte in the sample.
- Samplers installed through overlying water; control of sampler depths and thickness of layers is less certain than at other locations where the samplers were installed without significant overlying water.
- ² Average of duplicate samples

Porewater concentration calculated using equation:

(Mass in SPME PDMS Sorbent/((PI() $^{\circ}$ 0.15 $^{\circ}$ 2)-(PI() $^{\circ}$ 0.10 $^{\circ}$ 2)) *fiber length))/ KPDMS where K_{PDMS} is 6,761 L/kg for phenanthrene, 346,737 L/kg for PCB-52, and 870,964 L/kg for 2,3,7,8-TCDD.

Table 2
SPME PDMS Sorbent and Surface Sediment Analytical Results

Location				16A	ı-0608		16A-0609'			
	layer_sampled		Armor Layer	Cap Active Layer	Underlying Sediment	Surface Sediment	Armor Layer	Cap Active Layer	Underlying Sediment	Surface Sediment
	sys_loc_code		16A-0608-E1	16A-0608-E3	16A-0608-E2	16A-0608-S1	16A-0609-E1	16A-0609-E2	16A-0609-E3	16A-0609-S1
	sys_sample_code		16A-0608-E1-AS	16A-0608-E3-BS	16A-0608-E2-CS	16A-0608-S1-AS	16A-0609-E1-AS	16A-0609-E2-BS	16A-0609-E3-CS	16A-0609-S1-AS
S	ample deployment_date		6/4/2016	6/4/2016	6/4/2016	NA	6/3/2016	6/3/2016	6/3/2016	NA
	sample retrival_date	QAPP EDL Estimate	8/19/2016	8/19/2016	8/19/2016	8/19/2016	8/19/2016	8/19/2016	8/19/2016	8/19/2016
	matrix_code		SPME	SPME	SPME	SE	SPME	SPME	SPME	SE
	sample_type_code		N	N	N	N	N	N	N	N
	fiber_length (mm)		1522.1	1333.2	1559.1	-	1596.1	1597.6	1634.7	-
	report_result_unit									
Phenanthrene								T	1	
Mass in SPME PDMS Sorbent	ng	9.9	13.1 J+	5.43 J+	< 4 U	-	10.6 J+	12.2 J+	47	=
Concentration in Sediment	ng/g	-	-	-	-	546 J	-	-	-	1950 J
Calculated Concentration in Porewater	ng/L	-	32 J+	15 J+	< 9.7 U	-	25 J+	29 J+	110	-
PCB-52										
Mass in SPME PDMS Sorbent	pg	45	387	75.1 J+	34.4 J+	-	4630	26700	26500	=
Concentration in Sediment	pg/g	-	-	-	-	4120	-	-	-	5370
Calculated Concentration in Porewater	pg/L	-	19	4.1 J+	1.6 J+		210	1200	1200	-
2,3,7,8-TCDD										
Mass in SPME PDMS Sorbent	pg	17	< 3.99 U	< 3.47 U	< 4.29 U	=	< 8.19 U	18.7 Z	23 Z	=
Concentration in Sediment	pg/g	=	-	-	-	51.5	-	-	-	39.9
Calculated Concentration in Porewater	pg/L	-	< 0.077 U	< 0.076 U	< 0.080 U	-	< 0.15 U	0.34 Z	0.41 Z	-
Total Organic Carbon		·								
Total Organic Carbon ²	%	· ·				1.92				1.85

Notes:

Sample type: N - sample, FD - field duplicate, FB - field blank Matrix code: SPME - Solid Phase Micro Extraction , SE - sediment

PDMS - polydimethylsiloxane EDL - Estimated Detection Limit

mm - millimeter ng - nanogram

ng/g - nanogram per gram

ng/L - nanogram per liter

pg - picogram

pg/g - picogram per gram

pg/L - picogram per liter

L/kg - liter per kilogram

- U = The analyte was analyzed for, but was not detected above the reported sample detection limit.
- J = The analyte was positively identified; the associated numerical value is the approximate concentration of the analyte in the sample.
- J+ = The analyte was positively identified; the associated numerical value is the approximate concentration of the analyte in the sample and is potentially biased high.
- Z = EMPC-J = The analyte is identified as an estimated maximum possible concentration; the associated numerical value is the approximate concentration of the analyte in the sample.
- Samplers installed through overlying water; control of sampler depths and thickness of layers is less certain than at other locations where the samplers were installed without significant overlying water.
- ² Average of duplicate samples

Porewater concentration calculated using equation:

(Mass in SPME PDMS Sorbent/((PI() $^{\circ}$ 0.15 $^{\circ}$ 2)-(PI() $^{\circ}$ 0.10 $^{\circ}$ 2)) *fiber length))/ KPDMS where K_{PDMS} is 6,761 L/kg for phenanthrene, 346,737 L/kg for PCB-52, and 870,964 L/kg for 2,3,7,8-TCDD.

Table 2
SPME PDMS Sorbent and Surface Sediment Analytical Results

			16A	-0610		Field Blank	
	layer_sampled		Armor Layer	Cap Active Layer	Underlying Sediment	Surface Sediment	rieio biank
	sys_loc_code		16A-0610-E1	16A-0610-E2	16A-0610-E3	16A-0610-S1	
	sys_sample_code		16A-0610-E1-AS	16A-0610-E2-BS	16A-0610-E3-CS	16A-0610-S1-AS	16A-0BLK-E1-XF
s	ample deployment_date		6/3/2016	6/3/2016	6/3/2016	NA	6/3/2016
	sample retrival_date	QAPP EDL Estimate	8/19/2016	8/19/2016	8/19/2016	8/19/2016	8/20/2016
	matrix_code		SPME	SPME	SPME	SE	SPME
	sample_type_code		N	N	N	N	FB
	fiber_length (mm)		1109.6	1468.2	1593.9	-	1639.7
	report_result_unit						
Phenanthrene							
Mass in SPME PDMS Sorbent	ng	9.9	17.1 J+	4.73 J+	11.4 J+	-	4.91
Concentration in Sediment	ng/g	-	-	-	-	1310 J	-
Calculated Concentration in Porewater	ng/L	-	58 J+	12 J+	27 J+	-	11
PCB-52							
Mass in SPME PDMS Sorbent	pg	45	531	294	20000	-	28.3 Z
Concentration in Sediment	pg/g	-	-	-	-	16500 J	-
Calculated Concentration in Porewater	pg/L	-	35	15	920	-	1.3 Z
2,3,7,8-TCDD							
Mass in SPME PDMS Sorbent	pg	17	< 1.96 U	< 2.06 U	28	-	< 2.2 U
Concentration in Sediment	pg/g	=	=	=	=	167 J	=
Calculated Concentration in Porewater	pg/L	-	< 0.052 U	< 0.041 U	0.51	-	< 0.039 U
Total Organic Carbon							
Total Organic Carbon ²	%					6.06	

Notes:

Sample type: N - sample, FD - field duplicate, FB - field blank Matrix code: SPME - Solid Phase Micro Extraction , SE - sediment

PDMS - polydimethylsiloxane EDL - Estimated Detection Limit

mm - millimeter

ng - nanogram

ng/g - nanogram per gram

ng/L - nanogram per liter

pg - picogram

pg/g - picogram per gram

pg/L - picogram per liter L/kg - liter per kilogram

U = The analyte was analyzed for, but was not detected above the reported sample detection limit.

- J = The analyte was positively identified; the associated numerical value is the approximate concentration of the analyte in the sample.
- J+ = The analyte was positively identified; the associated numerical value is the approximate concentration of the analyte in the sample and is potentially biased high.
- Z = EMPC-J = The analyte is identified as an estimated maximum possible concentration; the associated numerical value is the approximate concentration of the analyte in the sample.
- Samplers installed through overlying water; control of sampler depths and thickness of layers is less certain than at other locations where the samplers were installed without significant overlying water.
- ² Average of duplicate samples

Porewater concentration calculated using equation:

(Mass in SPME PDMS Sorbent/((PI() * 0.15 $^{\circ}$ 2)-(PI() * 0.10 $^{\circ}$ 2)) *fiber length))/ KPDMS where K_{PDMS} is 6,761 L/kg for phenanthrene, 346,737 L/kg for PCB-52, and 870,964 L/kg for 2,3,7,8-TCDD.

Table 3 RM 10.9 Poling Results River Mile 10.9 Removal Action Lower Passaic River Study Area


Date Time Depth (ft) Thickness (ft) Thickness (ft Layer (ft) Comment Poling Approa Notes 06-Jul-16 11:13:20am Cap Edge (too deep) >36 ft A-10f A-11f 07-Jul-16 07-Jul-16 06:52:15am 06:55:09am 11:08:50am Foot Foot Boat 0.4 0.5 NM 1.0 06-Jul-16 A-3 06-Jul-16 11:15:51am Boat NM NM NM 12.6 06-Jul-16 06-Jul-16 06-Jul-16 Boat Boat Boat NM NM 12.5 14.5 8.5 8.4 A-4 11:20:08am NM NM 11:22:08am 11:26:03am A-06-Jul-16 03:23:44pm Boat ND ND A-8 06-Jul-16 03:29:26pm Boat 3.7 2.4 6.1 Sand and armor mixed A-9f B-1 B-10f Foot Boat Foot 07-Jul-16 06-Jul-16 06:50:22am 11:36:35am 0.7 NM 0.7 0 NM 07-Jul-16 06:45:59am 0.5 NM 06-Jul-16 11:38:29am Boat NM NM Boat Boat Boat NM ND NM 11:40:48am 03:33:58pm 8.1 Not found Not found B-3 B-4 06-Jul-16 06-Jul-16 NM NM NM ND No armor, sand at 7.5 ft B-5 06-Jul-16 03:36:52pm No armor B-6 B-7 06-Jul-16 03:39:24pm Boat NM NM NM 1.2 NM 0.7 NM 06-Jul-16 03:41:45pm Boat 4.8 06-Jul-16 07-Jul-16 06-Jul-16 03:44:37pm 06:44:36am 11:48:22am Boat Foot Boat B-8 B-9 NM NM C-2 06-Jul-16 11:50:47am Boat NM NM NM 8.7 2.5 ft silt observed on rod NM 2.1 1.9 0.7 NM 1.1 0.4 06-Jul-16 06-Jul-16 11:52:36am 03:59:31pm Boat Boat NM 4.2 7.6 7.3 4.3 C-3 Boat C-5 C-7f 06-Jul-16 04:03:14pm 07-Jul-16 06:38:07am Foot 0.4 1.1 Foot Boat Foot 06:39:43am 12:00:51am 06:31:22am C-8f D-1 07-Jul-16 06-Jul-16 1.1 NM 1.6 0.3 NM 7.6 NM D-10f 07-Jul-16 1.8 0.3 NM D-2 06-Jul-16 12:03:17am Boat NM NM D-3 06-Jul-16 12:06:10am Boat NM NM NM 9.5 D-4 D-5 D-6 12:11:47am 12:15:23am 04:12:19pm Boat Boat Boat NM NM NM NM NM NM NM NM NM 06-Jul-16 06-Jul-16 7.7 > 2 ft silt observed on rod 8.3 06-Jul-16 D-7 06-Jul-16 04:14:09pm Boat 2.2 2.2 2.1 6.4 D-8f D-9f 07-Jul-16 07-Jul-16 06-Jul-16 06:28:00am 06:29:10am 04:25:33pm Foot Foot Boat 0.5 1.2 0.3 0.3 5.4 3.4 0.8 1.6 06-Jul-16 04:30:54pm Boat Foot NM NM NM 07-Jul-16 06:18:53am 0.2 0.7 Foot Foot Boat 0.9 1.0 NM E-4f E-5f 07-Jul-16 06:20:42am 0.5 1.4 1.3 07-Jul-16 06:22:28am 0.3 NM 0 NM E-6 07-Jul-16 09:42:39am E-7 07-Jul-16 09:48:33am Boat 4.8 ND ND 6.8 10:00:03am 04:34:47pm 10:31:44am Boat Boat Boat E-8 F-1 NM NM NM NM NM NM Spotty armor area--edge of cap 1.0 6.7 07-Jul-16 NM NM NM 6.6 F-11 07-Jul-16 10:33:47am Boat NM NM NM 9.2 10:36:11am 04:36:41pm 05:50:32am Boat Boat Foot F-12 07-Jul-16 NM NM NM 9.1 06-Jul-16 07-Jul-16 4.2 0.5 8.2 0.8 1.5 0.3 07-Jul-16 05:51:36am Foot 0.6 0.3 1.5 F-5f 07-Jul-16 05:53:39am Foot 07-Jul-16 07-Jul-16 07-Jul-16 ND NM NM 0.8 NM NM 10:13:40am 10:16:19am Boat Boat 6.3 Boat 10:22:03am 07-Jul-16 10:29:39am Boat NM NM NM Boat Boat Foot NM 1.0 0.7 NM 0.1 0.2 04:51:36pm 04:54:19pm NM 1.6 G-1 0.9 G-3f 07-Jul-16 06:01:26am 0 G-4f 07-Jul-16 06:04:59am Foot 0 0.8 0.3 1.2 G-5 07-Jul-16 10:54:23am Boat NM NM NM 8.8 07-Jul-16 06-Jul-16 06-Jul-16 10:58:24am 04:59:41pm 05:02:43pm Boat Boat Boat NM 2.3 NM NM 1.3 NM G-6 H-1 H-2 NM H-3f 07-Jul-16 06:07:35am Foot ND ND H-4f H-5 H-6 07-Jul-16 07-Jul-16 07-Jul-16 06:08:58am 11:04:01am 11:06:14am Foot Boat Boat 0 NM NM ND NM NM ND NM NM 0.9 8.0 9.3 06-Jul-16 02:11:27pm Boat 0.8 1-2 06-Jul-16 02:16:56pm Boat 0.7 0.8 6.6 02:22:58pm 02:26:55pm Boat Boat ND 0.2 I-3 I-4 06-Jul-16 NM ND 9.2 Spotty armor area--edge of cap 06-Jul-16 1-5 06-Jul-16 05:09:08pm Boat 0.02 0.0 0.3 0.5 Off cap near transect J 06-Jul-16 02:37:26pm Boat NM ND Not found Not found Boat Boat Boat 6.7 NM NM 0.3 NM NM J-2 J-3 J-4 7.3 10.6 NM 06-Jul-16 02:52:36pm 8.1 J-5 06-Jul-16 05:39:40pm Boat NM NM NM 2.6 NM NM off cap off cap 07-Jul-16 07-Jul-16 07-Jul-16 11:11:36am 11:25:04am 11:27:50am Boat Boat Boat NM NM NM NM Not found Not found Not found Off cap near transect Y
Off cap near transect X
Off cap near transect X 07-Jul-16 07:01:33am Foot 0.4 X-2f 07-Jul-16 07:02:50am Foot 0.6 X-3f X-4f X-5f Foot Foot Foot 0.6 NM 0.6 Not found 0.7 Not found 07-Jul-16 07-Jul-16 07:04:18am 07:07:45am NM Off cap near transect X 0.1 NM Off cap near transect X 07-Jul-16 07:07:07am X-6 07-Jul-16 11:23:53am Boat NM NM NM 11.0 Boat Boat Boat X-7 X-8 NM NM NM NM NM NM 13.5 12.0 NM NM 07-Jul-16 11:33:33am NM 5.8 X-9 Y-1 07-Jul-16 11:13:25am Boat NM NM NM 13.1 07-Jul-16 11:15:06am 07-Jul-16 11:16:11am NM NM NM NM NM NM 9.6 15.5

Notes: ND--Not Distinguishable NM--Not Measured All depths measured from surface of water

Transects Corresponding SPME Stations:								
D604	G607	J610	A601					
E605	H608	X-Downstream Extent	B602					
F606	I609	YUpstream Extent	C603					

Figures

AECOM December 2016









Figure 2
Transect Poling Results, July 6-7, 2016
Mid-Point Check and Cap Inspection
LPR River Mile 10.9 Cap





Attachment A

Deployment Photographs June 3-5, 2016

AECOM December 2016

Client Name: DMI

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 06052016

Direction Photo Taken:

Northwest

Description:

Looking from 16A-0601 upriver (toward other stations) around Low tide.



Photo No.

Date: 06032016

Direction Photo Taken:

South

Description:

Looking downriver from above 16A-0608 around Low tide.



Client Name: DMI

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 06032016

Direction Photo Taken:

Northeast

Description:

Looking upriver from near 16A-0608



Photo No.

Date: 06042016

Direction Photo Taken:

East

Description:

Installed 16A-0601



Client Name: DMI

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 06052016

Direction Photo Taken:

North

Description:

Installed 16A-0602



Photo No.

Date: 06052016

Direction Photo Taken:

Northwest

Description:

Installed 16A-0603 & duplicates



Client Name: DMI Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 06042016

Direction Photo Taken:

Northwest

Description:

Installed 16A-0604




Photo No.

Date: 06042016

Direction Photo Taken:

Northwest

Description:

Installed 16A-0605



Client Name: DMI Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No. 9

Date: 06032016

Direction Photo Taken:

North

Description:

Installed station 16A-0606



Photo No. 10 **Date:** 06032016

Direction Photo Taken:

North

Description:

Installed station16A-0607



Client Name: DMI Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 06042016

Direction Photo Taken:

North

Description:

Installed Station 16A-0608



Photo No. 12 **Date:** 06032016


Direction Photo Taken:

North

Description:

Installed Station16A-0609

(Samplers submerged by incoming tide by the time this photo was taken)



Client Name: DMI

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 06032016

Direction Photo Taken:

Northeast

Description:

Installed Station16A-0610



Photo No. 14 **Date:** 06032016

Direction Photo Taken:

East

Description:

@ 12:42 PM observed stormwater discharge from culvert located on bank above 16A-0610.



Attachment B

Mid-Program Check Photographs July 6-7, 2016

AECOM December 2016

Client Name: DMI

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 07072016

Direction Photo Taken:

Northwest

Description:

Looking from station 16A-0601 upriver (toward other stations) around low tide.



Photo No. 2

Date: 07072016

Direction Photo Taken:

South

Description:

Looking downriver from above station 16A-0608 around low tide.



Client Name: DMI Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 07072016

Direction Photo Taken:

Northeast

Description:

Looking upriver from station 16A-0608 around low tide.



Photo No.

Date: 07072016

Direction Photo Taken:

West

Description:

Station 16A-0601



Client Name: DMI Site

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 07072016

Direction Photo Taken:

Northwest

Description:

Station 16A-0602



Photo No.

Date: 07072016

Direction Photo Taken:

Northwest

Description:

Station 16A-0603 (Right) & Station 16A-0603D (Left)



Client Name: DMI

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 07072016

Direction Photo Taken:

North

Description:

Station 16A-0604



Photo No.

Date: 07072016

Direction Photo Taken:

Northwest

Description:

Station 16A-0605



Client Name: DMI

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 07072016

Direction Photo Taken:

North

Description:

Station 16A-0606



Photo No. 10


Date: 07072016

Direction Photo Taken:

North

Description:

Station 16A-0607



Client Name: DMI Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 07072016

Direction Photo Taken:

North

Description:

Station 16A-0608



Photo No. 12 **Date:** 07062016

Direction Photo Taken:

North

Description:

Station16A-0609

(Samplers installed in water in June. Picture taken 35 min before low tide.)



Client Name: DMI Site Location: Lower Passaic River (River Mile 10.9) Project No. 60270961

Photo No. Date: 07062016

Direction Photo Taken:

North

Description:

Station16A-0610



Photo No. Date: 07062016

Direction Photo Taken:

West

Description:

Looking downriver toward station 16A-0609 from station 16A-0610.



Attachment C

August 2016 Check Photographs August 3, 2016

AECOM December 2016

Client Name: DMI

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 08032016

Direction Photo Taken:

West

Description:

16A-0601 at Low tide.



Photo No.

Date: 08032016

Direction Photo Taken:

West

Description:

16A-0602 at low tide.



Client Name: DMI Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 08032016

Direction Photo Taken:

Northwest

Description:

16A-0603 and duplicate at low tide



Photo No.

Date: 08032016

Direction Photo Taken:

Northwest

Description:

16A-0604 at low tide



Client Name: DMI

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 08032016

Direction Photo Taken:

Northwest

Description:

16A-0605 at low tide



Photo No.

Date: 08032016

Direction Photo Taken:

Northwest

Description:

16A-0606 at low tide



Client Name: DMI

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 08032016

Direction Photo Taken:

North

Description:

16A-0607 at low tide



Photo No.

Date: 08032016

Direction Photo Taken:

North

Description:

16A-0608 at low tide



		РНОТО	RAPHIC LOG
Client Name: DMI		Site Location: Lower Passaic River (River Mile 10.9)	Project No 60270961
Photo No. 9	Date: 08032016		
Direction Ph	noto Taken:		
North			
Description:		da	
16A-0609			
		31	-
		· \\	/
		Y/)	-
		V	

Attachment D

Retrieval Photographs August 19-22, 2016

AECOM December 2016

Client Name: Cooperating Parties Group

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 08202016

Direction Photo Taken:

West

Description:

Station 16A-0601




Photo No. 2

Date: 08202016

Direction Photo Taken:

Northwest

Description:



Client Name: Cooperating Parties Group

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 08202016

Direction Photo Taken:

Northwest

Description:

Station 16A-0603 (Right) & Station 16A-0603D (Left)



Photo No.

Date: 08202016

Direction Photo Taken:

North

Description:



Client Name: Cooperating Parties Group

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 08202016

Direction Photo Taken:

Northwest

Description:

Station 16A-0605



Photo No.

Date: 08192016

Direction Photo Taken:

North

Description:



Client Name: Cooperating Parties Group

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 08192016

Direction Photo Taken:

North

Description:

Station 16A-0607



Photo No.

Date: 08192016

Direction Photo Taken:

North

Description:



Client Name: Cooperating Parties Group

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 08192016

Direction Photo Taken:

North

Description:

Station16A-0609

(Samplers installed in water in June. Picture taken 10 min before low tide.)



Photo No. 10

Date: 08192016

Direction Photo Taken:

North

Description:



Client Name: Cooperating Parties Group

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 08202016

Direction Photo Taken:

NA

Description:

Representative photo of sediment sample being collected (station 16A-0604) within 8 inches of Armor layer sampler. Prior to sampler retrieval.



Photo No. 12

Date: 08192016

Direction Photo Taken:

NA

Description:

Representative photo of removed Henry sampler (station 16A-0607).



Client Name: Cooperating Parties Group

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No. 13 **Date:** 08212016

Direction Photo Taken:

NA

Description:

Removing SPME fibers from Henry sampler




Photo No. 14 **Date:** 08212016

Direction Photo Taken:

NA

Description:

Processing SPME fibers extracted from Henry Sampler.



Attachment E

Example Calculation

AECOM December 2016

Example Calculation for PCB-52 for armor layer sample 16A-0601-E1-AS

PDMS Volume

$$V_{PDMS} = \frac{1}{4} (\pi d_{Core}^2 - \pi d_{PDMS}^2) L_{PDMS}$$

Input		
Total Fiber Length (L):	1514.9	mm

Fiber Lengths:								
Sample Armor Layer		Cap Active Layer		Underlying Sediments		Field Blank		
Sample ID	15A-0602-EA-AS		15A-0602-E1-BS		15A-0602-E1-CS		15A-060	2-E1-XF
Total Fiber Length (L)	1514.9	mm	1594.4	mm	1599.7	mm	1639.7	mm

Core Diameter (d _{core})		PDMS Dia	ameter (d _{PDMS})	Length (L)	Volume (V _{PDMS})	
μm	mm	μm	mm	mm	mm³	μL
200	0.2	300	0.3	1514.9	59.5	59.5

Concentration in PDMS Sorbent

$$\mathsf{C}_{\mathsf{PDMS}} = \frac{C_{sample}}{V_{PDMS}}$$

Inputs:		
Sample Result (C _{sample}):	1740.0	pg
PDMS Volume (V _{PDMS}):	59.5	μL

Sample Result (C _{sample})		PDMS Volume (V _{PDMS})		Concentration in PDMS Sorbent (C _{PDMS})			
1740	pg	59.5	μL	29.2	pg/μL	29.2	μg/kg

Pore water Concentration

$$C_{PW} = \frac{C_{PDMS}}{K_{DPMS}}$$

Inputs:						
C _{PDMS}	29.2	μg/kg				
K _{PDMS} PCB-52	346737	L/kg				

K_{PDMS}						
Constituent log Kdpms ¹ Kdpms						
Phenanthrene	3.83	6761	L/kg			
PCB-52	5.54	346737	L/kg			
2,3,7,8-TCDD	5.94	870964	L/kg			
¹ From OAPP Worksheet #11						

Concentration in PDMS Sorbent (C _{PDN}	(S) Kdpms	Pore Water Concentration (C _{PW})		
29.2 μg/kg	346737	8.44E-05	ug/L	84 pg/L

Attachment F

Cap Inspection Photographs July 6-7, 2016

AECOM December 2016

Client Name: DMI

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 07072016

Direction Photo Taken:

Northwest

Description:

Annual Cap Inspection

Looking from station 16A-0601 upriver (toward other stations) around low tide.



Photo No.

Date: 07072016

Direction Photo Taken:

South

Description:

Annual Cap Inspection

Looking downriver from above station 16A-0608 around low tide.



Client Name: DMI Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 07072016

Direction Photo Taken:

Northeast

Description:

Annual Cap Inspection

Looking upriver from station 16A-0608 around low tide.



Photo No.

Date: 07062016

Direction Photo Taken:

West

Description:

Annual Cap Inspection

Looking downriver toward station 16A-0609 from station 16A-0610.



Client Name: DMI

Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 07062016

Direction Photo Taken:

South

Description:

Annual Cap Inspection

Shoreline at station 16A-0610 during low tide event.



Photo No.

Date: 07062016

Direction Photo Taken:

South

Description:

Annual Cap Inspection

Shoreline at station 16A-0609 during low tide event.



Client Name: DMI Site Location: Lower Passaic River (River Mile 10.9)

Project No. 60270961

Photo No.

Date: 07062016

Direction Photo Taken:

Southeast

Description:

Annual Cap Inspection

Shoreline at station 16A-0608 during low tide event.



Photo No. 10

Date: 07062016

Direction Photo Taken:

South

Description:

Annual Cap Inspection

Shoreline during low tide event.

